

# TATRA PHOENIX 8PFR43/35X3

## TATRA T158–8PFR43 41 355 8x8.2/35Z CAB-CHASSIS

### ENGINE

Type	PACCAR MX-13
Nos. of cylinders	6
Bore/stroke	130/162 mm
Swept volume	12,900 cm <sup>3</sup>
Power	std 355 kW / 1,600 min <sup>-1</sup> (390 kw As Option)
Torque	2,350 Nm / 900 - 1,365 min <sup>-1</sup>
Emission level	EURO V (SCR)
Air intake location options:	ROOF

### CLUTCH

Type:	SACHS MFZ 1x430, single clutch disc
-------	-------------------------------------

### GEARBOX

Type	ZF TRAXON 16TX 2640 TO (automated)
Intarder as option:	16TX2641TO (auto)

### AUXILIARY GEARBOX

Type	TATRA 2.30 TR 0.95/1.44
Number of gears	2
Gear ratio	0.945/1.435

### PTOs

On rear of engine (REPTO) as option	
On gearbox as option	
On auxiliary gearbox (transfer gearbox) as option	

### FRONT AXLE

Steered, driven with swinging half-axles, axle differential lock.	
Dis-engageable front drive.	
Air bellows and telescopic shock absorbers	
Stabiliser/torsion bar as option	

### REAR AXLE

Driven, with swinging half-axles, axle differential lock.	
"Light combined TATRA suspension" – air bellows with coil spring (inside), telescopic shock absorbers	
Stabiliser/torsion bar as option on 3rd axle	

### BRAKES

Wedge type self-adjustable drum brake on all axles, ABS.	
Four separate brake systems: service, emergency, parking and engine brake (MX Engine Brake). Spring brakes on axles 2 & 3.	
Transmission intarder as option.	

### STEERING

Integral power steering	Right Hand Drive ZF power assisted mechanical
-------------------------	--

### TYRES & RIMS

	front	rear
Tyres	385/65R22.5	DUAL 315/80R22.5
Rims	22.5x11.75	22.5x9.00
Rims in steel or alloy as option.		
With spare wheel		

### CABIN

COE tilt-cab electric / manual, std short (day) long (sleeper) version as option, air conditioned, two seats, air suspension driver's and passenger seat, central locking. UN-ECE R29 compliant.

### FUEL TANK & AdBlue

Steel, 540 litres (340L & 220L as option) + 45 litres AdBlue

### DIMENSIONS

Wheelbase (standard)	2,000 + 3,460 <sup>^</sup> + 1,450 mm
<sup>^</sup> options	3,660 / 4,362 mm
Chassis rear overhang	min/std 710 / 1,897 mm
Length (with std overhang and rear protection)	10,472 mm
Height	3,220 mm
Width (ADR)	2,500 mm
Track (on standard tyres) - front / rear	2,043 / 1,777 mm

### WEIGHT

ISO Kerb mass (front + rear)	8,390 + 3,990 = 12,380 kg
Payload (cab-chassis to GVM)	28,620 kg
GVM	41,000 kg
GCM	73,000 kg
Front axle max. permissible load	2 x 9,000 kg
Rear axle max. permissible load	2 x 11,500 kg

### ELECTRIC EQUIPMENT

Nominal voltage	24 V
Battery	2x12V 180 Ah
Alternator	24 V / 80 A (120A as option)

### VEHICLE PERFORMANCE

Max speed (with speed limiter)	100 km/h
Turning diameter (curb-curb)	24.0±0.5 m
Fording	800 mm

### FEATURES

Bullbar (with/without FUPD) as option	
Towing: Ringfeder 50mm pin coupling as option	

[www.tatratrucks.com.au](http://www.tatratrucks.com.au)

# OFFROAD TRUCKS AUSTRALIA PTY LTD

ABN 12 091 646 481

DL 16670

### HEAD OFFICE & SHOWROOM

25 Garnet Way (Cnr Eva St)  
MADDINGTON WA 6109  
PO Box 342  
FORRESTFIELD WA 6058  
T: (08) 9459 8911



[tatra@offroadtrucks.com.au](mailto:tatra@offroadtrucks.com.au)  
[www.offroadtrucks.com.au](http://www.offroadtrucks.com.au)

### MACKAY

26 Heidi Street  
Paget QLD 4740  
T: 0427 388 797